

WALKER BAG INSTRUCTION

Fabric: 2 pieces for front and back
14-15 inches in width
43-53 inches in length (+ one piece of batting,
if needed)
Velcro: 2 3-inch pieces (hook & loop)

NOTE: Batting or interfacing is used to help give the fabrics some body and thickness if using lightweight cotton fabric, etc. If you are using home dec fabric, this may not be needed as these fabrics have a tendency to be heavier in nature.

If using batting or an interfacing, sew or fuse to one piece of the fabric. Place the two pieces of fabric right sides together, sewing all the way around, leaving a four-six inch opening. Clip corners and turn fabric inside out. Press the open seam closed. (I use a piece of fusible tape to secure the open seam). Iron the flat piece of fabric.

Fold this flat piece of fabric in half to find the center. Measure 5" down from the center mark and 1 1/2" in from the side of your fabric. Sew one piece of your Velcro (ex. the hook part of the Velcro) and repeat for the Velcro that is the loop on the other side of your center mark. Repeat with the other strip of Velcro. When you look at your open flat piece of fabric you should then have four pieces of Velcro which will meet each other when the fabric is folded in half. This is how the bag will be attached to the walker.

To make the pockets, on the other side of the fabric fold up the fabric to where the top of the Velcro stitching is. The folded pocket will cover up the seams from the stitched Velcro on the other side.

Repeat for other pocket. Top stitch the length of the fabric to hold the pockets in place. Find the middle of the pocket and stitch again so you have now created two pockets.

Press again. ALL DONE!

NOTE: Please feel free to embroider, use decorative stitching, applique, whatever pleases you, to make these bags even more beautiful!

